PHŒNIX CONTACT

Electronic housing - ME 12,5 OT-MKDSO GN - 2906830

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

Housing upper part, for printed circuit terminal block connection

Product Features

- ☑ Tool-free mounting
- ☑ Large assembly area
- ☑ Low design width with a high number of positions
- ☑ Recessed labeling areas
- ☑ Same PCB geometry for all design widths
- ☑ Fast mounting on DIN rails according to EN 60715
- ☑ Inflammability class V0 according to UL 94
- ☑ Cost savings thanks to easy device production
- ☑ Material and part identification embossed on the housing (recyclability)
- ☑ Electronic components can be partially removed
- ☑ Metal foot catch
- ☑ Optional BUS connection integrated in the housing, for either parallel or serial contacting
- ☑ Functional earth ground contact (EMC) integrated in the housing base

Key commercial data

Packing unit	1 1
Minimum order quantity	10 1
GTIN	4 017918 126469
Weight per Piece (excluding packing)	9.65 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

General

Housing type	Component housing

Electronic housing - ME 12,5 OT-MKDSO GN - 2906830

Technical data

General

Housing material	Polyamide
Color	green

Dimensions

Constructional height	38.5 mm
Width	12.5 mm

Technical data

Inflammability class according to UL 94	V0
Number of positions	8

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27141190
eCl@ss 6.0	27141190
eCl@ss 7.0	27141190
eCl@ss 8.0	27141190

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC000886

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Electronic housing - ME 12,5 OT-MKDSO GN - 2906830

Approvals

Approvals

UL Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized